

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

AI
Claim 1 (Currently Amended). A Presealed System device, comprising:
a first sleeve;
a second sleeve; and
a resilient member having a first portion which separates the first sleeve from the second sleeve, wherein the first sleeve, the second sleeve and the resilient member pass through a boundary that separates two spaces from one another, the resilient member being located inside the boundary.

Claim 2 (Original). The Presealed System device of claim 1, wherein the first sleeve and the second sleeve are each PVC sleeves.

Claim 3 (Original). The Presealed System device of claim 1, wherein the resilient member includes: a rubber sleeve.

Claim 4 (Original) The Presealed System device of claim 1, wherein the resilient member further includes:
a second portion substantially perpendicular to the first portion, which is exterior to the first sleeve and the second sleeve.

Claim 5 (Currently Amended). The Presealed System device of claim 4, wherein the resilient member further includes:
a third portion extending outward from the second portion.

Claim 6 (Original). The Presealed System device of claim 5, wherein the third portion includes: a washer configuration.

Claim 7 (Currently Amended). The Presealed System device of claim 5, wherein the first portion, the second and the third portion includes: a substantially \pm cross-sectional shape in the form of a cross.

Claim 8 (Original). The Presealed System device of claim 5, wherein the third portion includes: a raised ridge on a surface portion of the third portion.

Claim 9 (Original). The Presealed System device of claim 1, wherein the boundary is a wall.

Claim 10 (Original). The Presealed System device of claim 1, wherein the boundary is a floor.

Claim 11 (Original). The Presealed System device of claim 1, wherein the boundary includes: concrete.

Claim 12 (Original). The Presealed System device of claim 1, further comprising: a fire stop adjacent to the second sleeve.

AI
cont

Claim 13 (Original). The Presealed System device of claim 1, further comprising:
a plumbing pipe inserted through the first sleeve, the resilient member and the second sleeve, wherein the resilient member forms a seal about the pipe which is substantially maintained during expansion and contraction of the Presealed System device during daytime and nighttime temperature changes and heating and cooling conditions.

Claim 14 (Currently Amended). The Presealed System device of claim 1, further comprising:

a conduit inserted through the first sleeve, the resilient member and the second sleeve, the pipe allowing electrical lines to pass therethrough, wherein the resilient member forms a seal about the conduit which is substantially maintained during expansion and contraction of the Presealed System device during daytime and nighttime temperature changes and heating and cooling conditions.

Claim 15 (Currently Amended). A Presealed System device system for walls and floors, comprising in combination:

a first sleeve extending through one side of a boundary, the boundary being selected from at least one of a wall, and a floor;

a second sleeve extending through a second side of the boundary opposite the first side;

a resilient member, located in side the boundary, having a first portion which separates the first sleeve from the second sleeve, the first sleeve, the second sleeve and the resilient member form a through-hole opening through the boundary; and

a pipe passing through the through-hole in the boundary, the pipe being selected from at least one of a plumbing pipe and an electrical conduit.

Claim 16 (Currently Amended). The Presealed System device system of claim 15, wherein the resilient member includes:

an inwardly protruding portion being the first portion, a second portion substantially adjacent to the first portion and positioned exterior to the first sleeve and the second sleeve, and a third portion extending away from and being substantially perpendicular to the second portion, the first and the second and the third portions forming a substantially π cross-sectional shape in the form of a cross.

Claim 17 (Original). The Presealed System device system of claim 15, further comprising: a fire stop adjacent to the second sleeve.

Claims 18-25 (Currently Cancelled).

Claim 26 (New). A Presealed System device, comprising:
a first sleeve;
a second sleeve; and
a resilient member having: a first portion which separates the first sleeve from the
second sleeve, wherein the first sleeve, the second sleeve and the resilient member pass
through a boundary that separates two spaces from one another; a third portion having
including a raised ridge on the surface portion of the third portion, and extending outward
from the second portion.

Al
Conto
Claim 27 (New). A Presealed System device system for walls and floors, comprising in
combination:
a first sleeve extending through one side of a boundary, the boundary being
selected from at least one of a wall, and a floor;
a second sleeve extending through a second side of the boundary opposite the first
side;
a resilient member having a first portion which separates the first sleeve from the
second sleeve, the first sleeve, the second sleeve and the resilient member form a
through-hole opening through the boundary, and a third portion having including a raised
ridge on the surface portion of the third portion, and extending outward from the second
portion; and
a pipe passing through the through-hole in the boundary, the pipe being selected
from at least one of a plumbing pipe and an electrical conduit.
